



SECTION VIEW

1. EMBEDDED PARTICULATE / CLEANLINESS PER 01-02-WI AND 01-14-WI.
2. FLASH .010 MAX., FIRMLY ATTACHED.
3. GATE + OR - .010 MAXIMUM.
4. SINK IN INSIDE DIAMETER .008 MAXIMUM.
5. MAT'L: TEKNOR APEX 95A0937C-80NT OR EQUIVALENT. VIRGIN W/CERTS.
6. DOUBLE BAG PARTS IN 1.5MM P.E. BAGS.
7. INSPECT PER MIL-STD 105D AT 4.0 AQL.
8. PARTS TO BE MANUFACTURED IN CONTROLLED ENVIRONMENT.
9. COSMETIC CRITERIA PER 01-02-WI, CONNECTOR BODY IS CLASS II-B.

 INDICATES INSPECTION DIMENSION.

FOR REFERENCE ONLY

SEE NOTES 095

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±.015
ANGULAR: ± .5°
ONE DECIMAL ±.015
TWO PLACE DECIMAL ±.010
THREE PLACE DECIMAL ±.005
INTERPRET GEOMETRIC
TOLERANCING PER:

MATERIAL

APPROVED

WAYNE TOMBLIN

BREVET, INC.

TITLE: **504 "T" CONNECTOR
3/16 X 3/16 X 3/16
.062 WALL TUBING**

ORDER NO.

DWG. NO.

504-333-N-03

REV

B